

MAGNETIC HOLE CUTTING MACHINE KA35

GENERAL SAFETY INSTRUCTIONS





IMPORTANT SAFETY INSTRUCTIONS AND INFORMATION FOR POWER TOOLS

- KNOW YOUR POWER TOOL. Read and understand the safety and operating instructions, learn its application and limitations.
- EARTH ALL TOOLS. Ensure that (where applicable) suitable earthed cables/cords and plugs are used and correctly connected. Always check cable plug for any damage.
- KEEP GUARD IN PLACE. Fit and keep guards in place (where applicable). Ensure correct adjustment and alignment.
- KEEP WORK AREA CLEAN. The footprint oft he magnet must be clean (no chips, no rust, no dust).
- AVOID DANGER. Don't use power tools in damp or wet locations or expose them to rain. Keep work area well lighted. Provide adequate surrounding work space. Keep the unit and the work place as clear of dirt and swarf as possible.
- WEAR PROPER APPAREL. Do not wear loose clothing, gloves, neckties or jewellery (rings, wristwatches) to get caught in moving parts. NONSLIP footwear is recommended. Wear protective hair covering to contain long hair, roll long sleeves above the elbow.
- USE SAFTEY GOGGLES. (Head Protection). Wear approved safety goggles at all times. Everyday eyeglasses only have impact resistant lens, they are NOT safety glasses. Also, use face or dust mask if cutting operation is dusty, and ear protectors during extended peri-
- SECURE WORK. Use clamps or a vice to hold work when practical. It's safer and frees both hands to operate tool. Secure the unit with safety chain/carabina when working overhead or vertical.
- $\ensuremath{\textbf{DON'T}}$ $\ensuremath{\textbf{OVERREACH}}.$ Keep proper footing and balance at all times.
- MAINTAIN TOOLS WITH CARE. Keep tools sharp and clean for best and safest performance. Follow instructions for lubricating and changing accessories. Regular maintenance is essential. Check nuts, screws, bolts for tightness.
- 11. DISCONNECT TOOLS. Before servicing; when changing accessories such as cutters, etc.
- USE RECOMMENDED ACCESSORIES. Never use blunt Cutters/ Drills.
- CHECK DAMAGED PARTS. Before further use of the tool, a guard or other part that is damaged should be carefully checked to ensure that it will operate properly and perform its intended function. Check for alignment of moving parts, binding of moving parts, breakage of parts mounting, and any other conditions that may affect operation. A guard or other part that is damaged should be properly repaired or
- 14. NEVER LEAVE TOOL RUNNING UNATTENDED. Turn power off. Don't leave tool until it comes to a complete stop.
- KEEP CHILDREN AWAY. Do not let visitors contact tool or extension cord. All visitors should be kept away from work area.
- STORE IDLE TOOLS. When not in use, tools should be stored in dry, and high or locked-up place out of reach of children.
- DON'T FORCE TOOL. It will do the job better and safer at the rate for which it was intended.
- DON'T ABUSE CORD. Never carry tool by cord or yank it to disconnect from receptacle. Keep cord from heat, oil and sharp edges quality, high-performance and reliable tools. Karnasch Professional Tools offers all that matters!
- REMOVE ADJUSTING KEYS AND WRENCHES. Form habit of chekking to see that keys and adjusting wrenches are removed from tool before turning it on.
- AVOID UNINTENTIONAL STARTING. Don't carry plugged-in tool with 20. finger on switch. Be sure switch is off when plugging in.
- 21. OUTDOOR USE EXTENSION CORDS. When tool is used outdoors, use only extension cords intended for outdoors and so marked.
- 22. STAY ALERT. Watch what you are doing. Use common sense. Do not operate tool when you are tired.
- 23. AVOID USING A POWER TOOL FOR APPLICATIONS OTHER THAN THOSE SPECIFIED. Never use a power tool for applications other than those specified in the instruction manual.

- **ENSURE SAFE OPERATION THROUGH CORRECT HANDLING. Secure** safe operation through correct handling by observing the instructions described herein. Do not employ accessories other than those specified herein; otherwise, a hazardous condition may be created. Never allow a power tool to be used by persons not familiar with correct handling (such as children) or those who cannot handle the tool correctly.
- CONFIRM THAT NO ITEMS SUCH AS AN ELECTRIC CABLE OR CONDUIT ARE BURIED INSIDE. In places where live wiring may be hidden behind a wall, floor, ceiling, etc. do not hold or contact any metal parts of the tool. In such cases metal parts could become electrically live and present a serious shock hazard.
- KEEP THE RIGHT PARTS IN THE RIGHT POSITIONS. Do not remove covers and screws which have been factory-mounted. They perform important retrospective roles. Keep them in the right positions.
- SHOULD THE PLASTIC HOUSING OR HANDLE OF A POWER TOOL BE CRACKED OR DAMAGED, DO NOT USE IT. Since cracked or deformed parts may lead to an operator receiving an electric shock, do not use such a power tool. Immediately have it repaired.
- SECURELY MOUNT ACCESSORIES AND BLADES TO THE TOOL MAIN BODY. Extra care must be taken when using tools on elevated location (such as a roof, ladder, scaffold or the like) to prevent injury to someone on a lower level in the event of a dropping tool and / or an accessory. Secure unit with safety chain/carabina.
- 29. ALWAYS KEEP THE MOTOR AIR VENT FULLY OPENED. A constantly open motor air vent is necessary to allow air to come in and out for cooling the motor. Do not allow it to become clogged up, even if the dust is blown through it.
- 30. OPERATE POWER TOOLS AT THE RATED VOLTAGE. Operate power tools at voltages specified on their nameplates.
- 31. NEVER TOUCH THE MOVING PARTS. Never touch the moving parts such as bits, cutters, drills, taps, etc.
- STOP OPERATION IMMEDIATELY IF ANY ABNORMALITY IS **DETECTED.** Should a power tool be detected as out of order or should other abnormalities be observed during operation, stop using the tool immediately
- 33. NEVER LEAVE TOOL RUNNING UNATTENDED. TURN POWER OFF. Don't leave tool until it comes to a complete stop.
- CAREFULLY HANDLE POWER TOOLS. Should a power tool be dropped or struck against hard materials inadvertently, it may be deformed, cracked, or damaged.
- DO NOT WIPE PLASTIC PARTS WITH SOLVENT. Solvents such as gasoline, thinners, benzene, carbon tetrachloride, and alcohol may damage and crack plastic parts. Do not wipe them with solvents. Wipe plastic parts with a soft cloth lightly dampened with soapy water.
- REPAIRS TO MACHINE are to be carried out by qualified agent and genuine spare parts are always to be used.
- WARNING: Under no circumstances try to remove turnings or swarf from the cutter when machine is in operation. NEVER introduce any body parts to moving parts of the machine, when it is switched on. This document is issued for general information and instruction and as such does not constitute a specification of the equipment. Only use faultless and sharp drilling tools and avoid that the machine stops due to overload.
- ATTENTION: When fitting drills or cutter arbors into morse taper drive shafts, ensure morse taper and cone are free of grease and
- REMOVING MORSE TAPER TOOLS FROM MACHINE DRIVE SHAFT. Always ensure power is switched off or unplug mains cable. Put the drill drift in the opening of the gearbox collar. If you cannot insert the drill drift through the work spindle, turn the work spindle slightly. Remove the tool from the work spindle by a slight impact on the drill drift.



40. THE MAXIMUM MAGNETIC HOLDING FORCE OF THE MACHINE IS OBTAINED FROM A MATERIAL THICKNESS OF 15 MM. Reduce feed at thicknesses below 15mm. Below 10mm material thickness magnetic hole cutting machines should not be used.



KARNASCH PROFESSIONAL TOOLS® CNC TOOLS DIVISION

Siemensstraße 1 D-68542 Heddesheim

KARNASCH PROFESSIONAL TOOLS® INDUSTRIAL TOOLS DIVISION

Straße des Friedens 10 D-15848 Tauche / OT Görsdorf

CONTACT

Phone: +49 (0) 6203 4039-0 Fax: +49 (0) 6203 41590 E-Mail: info@karnasch.tools

